



CONTURAX®

Product overview

CONTURAX® – standard length

- Standard length = 1,500 mm
- Different lengths on request. Successful technical review provided.

Length overview






Outside Diameter OD [mm]	Wall Thickness WT [mm]	Length L [mm]
< 6.00		1,200 – 1,600
6.00 – 10.00		1,200 – 1,600
> 10.00 – 30.00	≥ 1.80	1,200 – 3,000
> 30.00 – 50.00	≥ 2.00	1,200 – 2,500
50.00 – 150	≥ 2.00	1,000 – 4,000

CONTURAX® – minimum order quantities

- Standard dimensions
 - 1 carton









CONTURAX® – specifications

Profile Type	Profile Number	Dimensions and Tolerances [mm]	Pieces / kg per Carton
	001	W 25.00 ± 1.50	9 / 9.3 kg
	002	W 31.00 ± 2.00	6 / 8.7 kg
	003	W 10.00 ± 0.50 W 29.00 ± 1.00	56 / 7.3 kg 9 / 9.2 kg
	004	W 30.00 ± 2.00 / ID 17.00 ± 2.00	6 / 7.5 kg
	006	OD 22.00 / WT 1.00 OD 30.00 / WT 2.00 OD 40.00 / WT 2.00 OD 50.00 / WT 2.50 OD 60.00 / WT 2.50 OD 70.00 / WT 2.50 OD 80.00 / WT 2.50 OD 100.00 / WT 3.00 min. OD for special lengths 30.00 mm / WT 2.00 or larger	35 / 9.0 kg 16 / 11.0 kg 16 / 16.2 kg 12 / 19.2 kg 9 / 16.6 kg 4 / 8.4 kg 4 / 10.0 kg 4 / 15.5 kg

W: width, OD: outer diameter, ID: inner diameter, WT: wall thickness

CONTURAX® – specifications

Profile Type	Profile Number	Dimensions and Tolerances [mm]	Pieces / kg per Carton
	028	H 7.50 / W 15.00 H 12.00 / W 25.00 H 14.50 / W 29.50	45 / 14.6 kg 18 / 14.5 kg 15 / 17.1 kg
	033	W 23.00 ± 1.00 W 27.00 ± 1.00 W 35.00 ± 1.50	12 / 16.5 kg 9 / 17.8 kg 4 / 13.2 kg
	041	SL 29.00 ± 1.00	9 / 12.0 kg
	049	H 12.00 / W 30.00	21 / 20.5 kg
	072	OD1 40.00 / OD2 30.00 / WT ~ 2.00 OD1 140.00 / OD2 68.00 / WT ~ 3.30	24 / 16.7 kg 2 / 7.4 kg
	073	OD1 140.00 / OD2 68.00 / WT ~ 3.30	2 / 11.0 kg








H: height, W: width, SL: side length, OD: outer diameter, ID: inner diameter, WT: wall thickness

CONTURAX® – minimum order quantities

- Special dimensions
 - between 500 – 1,000 kg
(depending on the profile)



CONTURAX® – specifications







Profile Type	Profile Number	Dimensions and Tolerances [mm]	Pieces / kg per Carton
	005	W 25.00 ± 1.50 / ID 17.00 ± 1.00	9 / 9.5kg
	008	W 30.00 ± 2.00 / ID 17.00 ± 2.00	20 / 18.5kg
	009	W 26.00 ± 1.00	6 / 11.0 kg
	010	W 20.00 ± 1.50 W 30.00 ± 2.00	42 / 14.0 kg 9 / 6.6 kg
	013	H 15.00 ± 1.50 / W 25.00 ± 1.80 H 16.00 ± 1.60 / W 32.00 ± 2.00	18 / 21.2 kg 10 / 14.3 kg
	017	W 15.00 ± 1.00 W 20.00 ± 1.00 W 25.00 ± 1.50 W 30.00 ± 1.50 W 35.00 ± 1.50	30 / 22.3 kg 16 / 21.2 kg 9 / 18.1 kg 6 / 17.0 kg 4 / 15.4 kg
	020	OD 24.00 ± 0.80 / WT 1.00 ± 0.20 / 12 bars OD 40.00 ± 1.50 / WT 2.00 ± 0.40 / 14 bars OD 60.00 ± 1.50 / WT 2.50 ± 0.40 / 14 bars OD 80.00 ± 1.50 / WT 3.00 ± 0.40 / 18 bars	30 / 11.2 kg 16 / 13.4 kg 9 / 15.1 kg 4 / 11.3 kg

H: height, W: width, OD: outer diameter, ID: inner diameter, WT: wall thickness

CONTURAX® product overview, March 2013









© SCHOTT AG

CONTURAX® – specifications

Profile Type	Profile Number	Dimensions and Tolerances [mm]	Pieces / kg per Carton
	021	D 25.00 ± 1.00	TBD
	024	OD 24.00 / WT ~ 1.00 / 12 bars short/long OD 30.00 / WT ~ 1.20 / 12 bars short/long	36 / 8.8 kg 16 / 7.5 kg
	034	W 40.00	20 / 13.2 kg
	035	W 35.00	12 / 13.0 kg
	036	H 20.00 / W 49.50	15 / 30.6 kg
	037	OD 135.00 ± 1.00 / WT 5.00 ± 0.70 / 410 striations	2 / 13.5 kg

H: height, W: width, D: diameter, OD: outer diameter, WT: wall thickness, TBD: to be determined

CONTURAX® – specifications








Profile Type	Profile Number	Dimensions and Tolerances [mm]	Pieces / kg per Carton
	038	W 30.00 ± 1.00 / WT max. 2.50 ± 0.30 / 60 striations W 40.00 ± 1.00 / WT max. 2.50 ± 0.30 / 60 striations W 60.00 ± 1.50 / WT max. 3.00 ± 0.40 / 60 striations W 136.50 ± 1.50 / WT min. 4.50 ± 0.50 / 80 striations	16 / 10.6 kg 16 / 15.0 kg 9 / 15.7 kg 2 / 11.5 kg
	040	W 35.00 ± 1.00	6 / 10.2 kg
	042	H 6.10 / W 18.00	50 / 16.3 kg
	043	H 5.90 / W 18.10	50 / 15.4 kg
	044	H 4.80 / W 18.20	50 / 14.8 kg
	046	H 5.80 / W 18.50	28 / 8.1 kg
	047	H 8.00 / W 30.00	TBD
	048	H 10.70 / W 40.00	14 / 14.0 kg

H: height, W: width, WT: wall thickness, TBD: to be determined

CONTURAX® product overview, March 2013








© SCHOTT AG

CONTURAX® – specifications

Profile Type	Profile Number	Dimensions and Tolerances [mm]	Pieces / kg per Carton
	050	H 11.00 / W 39.50	8 / 11.0 kg
	053	W 100.00 / WT 3.00 / 30 bars W 140.00 / WT 3.00 / 30 bars	4 / 13.9 kg 4 / 21.4 kg
	054	H 5.00 / W 6.00	TBD
	056	SL 30.00	9 / 17.7 kg
	057	H 6.00 / W 18.00	140 / 10.8 kg
	058	W 27.57 / ID 11.44	9 / 11.7 kg
	059	H 22.60 / W 30.00	9 / 13.6 kg







H: height, W: width, SL: side length, ID: inner diameter, WT: wall thickness, TBD: to be determined

CONTURAX® – specifications

Profile Type	Profile Number	Dimensions and Tolerances [mm]	Pieces / kg per Carton
	064	TBD	TBD
	065	H 4.00 / W 9.00	90 / 10.8 kg
	066	H1 5.00 / H2 10.00 / W 30.00	15 / 11.0 kg
	067	H 7.50 / W 18.00	36 / 14.0 kg
	068	W 10.00 W 25.00	48 / 14.0 kg 12 / 16.8 kg
	069	H 2.00 / W 3.00	562 / 12.0 kg
	070	H 14.00 / W 40.00	12 / 11.8 kg






H: height, W: width, TBD: to be determined

CONTURAX® – specifications

Profile Type	Profile Number	Dimensions and Tolerances [mm]	Pieces / kg per Carton
	074	H 5.50 / W 10.00 H 8.40 / W 15.00	84 / 12.2 kg 45 / 15.1 kg
	075	H 13.50 / W 30.00	18 / 14.8 kg
	076	W 20.00 / ID 10.00	36 / 18.4 kg
	077	H 16.50 / W 30.00 H 21.80 / W 40.00	15 / 15.3 kg 8 / 14.5 kg
	079	W 17.00 / ID 10.00	25 / 10.9 kg
	080	W 16.60 / ID 9.00	25 / 8.2 kg

H: height, W: width, ID: inner diameter

CONTURAX® – specifications

Profile Type	Profile Number	Dimensions and Tolerances [mm]	Pieces / kg per Carton
	082	OD1 200.00 / OD2 100.00 / WT ~ 4.00 / 96 grooves	2 / 13.8 kg
	088	H 8.00 ± 0.25	50 / 8.5 kg
	094a	H 25.00 / W 60.00 / ID 10.50	6 / 18 kg 6 / 18.6 kg 4 / 12.4 kg
	094b	H 25.00 / W 60.00	6 / 18 kg 6 / 18.6 kg 4 / 12.4 kg
	095	W 9.00 / ID 0.60 W 19.50 / ID 1.50	56 / 15.1 kg 16 / 19.4 kg

H: height, W: width, OD: outer diameter, ID: inner diameter, WT: wall thickness

Tubing

SCHOTT North America, Inc.

555 Taxter Road

Elmsford, NY 10523

USA

www.us.schott.com/tubing/design

Nikhil Krishna

Phone +1 (914)831 2265

Fax +1 (914)831 2201

nikhil.krishna@us.schott.com